

# DUPLICATE

Rec'd PCT/PTO 27 APR 2005


(12) INTERNATIONAL PUBLICATION PUBLISHED UNDER THE PATENT

OPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



10/532882



(43) International Publication Date  
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number  
**WO 2004/040058 A1**

(51) International Patent Classification<sup>7</sup>: D21B 1/02, 1/12

(21) International Application Number:  
PCT/SE2003/001614

(22) International Filing Date: 17 October 2003 (17.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
SE 0203176-3 29 October 2002 (29.10.2002) SE

(71) Applicant (for all designated States except US): METSO  
PAPER, INC. [FI/FI]; P.O. Box 1220, FI-00101 Helsinki  
(FI).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NL, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR PRODUCTION OF PULP



(57) Abstract: The present invention relates to an apparatus for separating steam from a mixture of steam and fibres, comprising an elongated feeding compartment (12) having an inlet and feeding means (10) for feeding a mixture through said inlet. The feeding means comprises a tubular section (18) which is curved such that the mixture in the tubular section (18) is separated during influence of centrifugal forces in a heavy steam-less fraction of fibres in an outer layer (20) and in a light fibre-free fraction of steam in an inner layer (22). The tubular section is arranged in such a way that heavy fraction of fibres is fed through the inlet peripherally (P). The separated light fraction of steam is fed against the centre (C) of the compartment and removed through an outlet (23, 24) of the apparatus. The present invention also relates to a feeding means (10) for use in an apparatus as defined above and a method.

WO 2004/040058 A1

## APPARATUS AND METHOD FOR PRODUCTION OF PULP

The present invention relates to an apparatus for separating steam from a mixture of steam and fibres, feeding means for use in the apparatus, and also a method for supplying a mixture of steam and fibres to an apparatus for separating steam from a mixture of steam and fibres.

10 Conventionally, a mixture of steam and fibres is supplied to a cyclone that separates a fraction of steam from a fraction of fibres and supplies the fraction of fibres to a feeding machine for further transportation of the fraction of fibres to a refiner in production of pulp. The  
15 cyclone has an outlet arranged radially against the circumference of the feeding machine for supplying the fraction of fibres in a direction against the centre of the feeding machine. Steam is removed from an outlet in the centre of the cyclone and the fraction of fibres is added  
20 to the feeding machine. The feeding machine comprises a conveyor worm that brought the fraction of fibres further to a refiner.

However, clogging of the cyclone is a problem, although  
25 there exists screening devices in the cyclone that should prevent this. One reason is that the loading of fibres is large in the lower part of the cyclone. The clogging also depends on that extractive matters, that are extremely sticky, adheres to the fibres and easily makes them to  
30 create deposits in the cyclone. Yet a problem is that the residence time for the fibres in the cyclone might be far too long, whereby the fibres becomes discoloured undesirably much before they reach the subsequent refiner stage. This results in an increased need for bleaching.

The present invention aims to accomplish a simple and improved separation of a mixture of fibres and steam, and thereby a more efficient and favourable feeding of fibres  
5 for further transportation to a refiner in production of pulp. Yet another object is to minimize the residence time of the fibres at separation of fibres and stem, and thereby avoid additional need for bleaching.

10 This object is achieved with the apparatus for separating steam from a mixture of steam and fibres according to the present invention. The apparatus comprises an elongated feeding compartment having an inlet arranged between the short sides of the elongated feeding compartment and  
15 feeding means for feeding a mixture of steam and fibres through said inlet. The feeding means comprises a tubular section which is curved such that the mixture of steam and fibres during passage in the tubular section is separated during influence of centrifugal forces in a substantially  
20 relatively heavy steam-less fraction of fibres in a radially outer layer and in a substantially light fibre-free fraction of steam in a radially inner layer. The tubular section is arranged in such a way that heavy fraction of fibres is fed through the inlet peripherally  
25 into the elongated feeding compartment of the apparatus, while the separated light fraction of steam is fed through the inlet against the centre of the elongated feeding compartment and removed through an outlet of the apparatus.

30

Through the design of the curved portion of the tubular section of the feeding means in accordance with the present invention, a more efficient and improved separation of fibres and steam can be done, without

appreciably needing to change the design of apparatus. The invention makes it possible to totally eliminate the need for a cyclone for separation of steam and fibre, and also for supply of fibre to the apparatus. This results in that the residence time during transportation to subsequent refiner can be minimized, whereby the requirement for strengthened bleaching of the fibres can be avoided. Thus, according to the present invention the apparatus works as a combined feeding machine for fibres and simultaneously as a separator of steam.

Preferably, in an outer tubular portion of the feeding means, which outer portion is adjacent an opposite end compared to the end of the curved tubular section which is connected to the inlet, the feeding means has a substantially straight, linear and non-curved extension. The feeding means might extend substantially perpendicular to the longitudinal extension of the apparatus. However, the feeding means is suitably arranged with an inclined extension in relation to the longitudinal extension of the apparatus, which extension preferably forms an angle between 75-90°, and most preferable an angle between 80-85°, in relation to the longitudinal extension of the apparatus. The inlet of the feeding means is suitably arranged tangentially at the circumference of the apparatus. The inlet and the feeding means can have a circular, quadratic or rectangular cross-sectional area. Preferably, the cross-sectional area of the inlet and the feeding means is quadratic or rectangular. A length of the curved section is adapted such that the velocity difference, between the velocity of the fibres in the feeding means in relation to the velocity of the conveyor worm in the apparatus, is minimized.

As mentioned above, both fibre and steam are fed to the apparatus. The mixture of steam and fibres is separated at passage in the curved tubular section, whereby a substantial relatively heavy steam-less fibre fraction  
5 forms a radially outer layer at the inlet that is fed peripherally in the apparatus. A substantially light fibre-free fraction of steam forms, at a passage in the curved tubular section, a radially inner layer that at the inlet is fed against the centre of the apparatus. Then the  
10 steam is removed from the centre of the apparatus through an axial outlet, or alternatively, through a radially outlet, arranged at the apparatus. The fraction of fibres at the circumference of the apparatus is conveyed further by way of a conveyor worm, arranged axially in the  
15 apparatus, against a subsequent refiner.

In the case the steam is discharged through a radially outlet at the apparatus, this is done from a rear chamber arranged in the apparatus, where steam is flowing through  
20 a gap formed between the shaft of the apparatus and an inwards wall section radially extending from an inner surface in the apparatus.

The present invention also relates to a feeding means for use in an apparatus as defined above, for feeding a  
25 mixture of steam and fibres through the inlet of the apparatus. The feeding means comprises a tubular section which is curved such that the mixture of steam and fibres during passage in the tubular section is separated during  
30 influence of centrifugal forces in a substantially relatively heavy steam-less fraction of fibres in a radially outer layer and in a substantially light fibre-free fraction of steam in a radially inner layer. The feeding means according to the present invention can

suitably be used as replacement of existing feeding means for feeding mixtures of fibres and steam to apparatuses, such as feeding machines, which are in operation today. Advantageous features of the feeding means in itself have  
5 been described above and are further explained in the following detailed description and in the appended claims.

The present invention also relates to a method for feeding a mixture of steam and fibres to an elongated feeding  
10 compartment of an apparatus for separating steam from a mixture of steam and fibres. The mixture of steam and fibres are fed via a feeding means through an inlet arranged between the short sides of the elongated feeding compartment. The feeding means comprises a tubular section  
15 which is curved, whereby the mixture of steam and fibres at passage in the tubular section is brought to separate during influence of centrifugal forces in a substantially relatively heavy steam-less fraction of fibres in a radially outer layer and in a substantially light fibre-free fraction of steam in a radially inner layer. The  
20 tubular section is arranged in such a way that heavy fraction of fibres is fed through the inlet peripherally into elongated feeding compartment of the apparatus, while the separated light fraction of steam is fed through the  
25 inlet against the centre of the elongated feeding compartment and removed through an outlet of the apparatus.

The present invention will now be described more detailed in embodiments, with reference to the accompanying  
30 drawings, without making a restricted interpretation of the invention thereto, where,

fig. 1A shows schematically an apparatus in a partly sectional longitudinal view,

fig. 1B shows schematically an apparatus in a partly sectional longitudinal view according to an alternative embodiment of the apparatus of fig. 1A, and

fig. 1C shows the apparatus according to fig. 1A  
5 and 1B in a cross-section A-A.

Corresponding features of the embodiments illustrated in the figs. have been denoted with the same reference numerals.

10

Fig. 1A-C shows an apparatus comprising feeding means 10 for feeding a mixture of steam and fibres to an elongated feeding compartment 12 according to the present invention. The feeding means 10 is arranged to an inlet 14 at the  
15 circumference 16 of the compartment 12. The inlet 14 is arranged between the short sides 15, 15' of the elongated feeding compartment 12, through which inlet steam and fibres are fed to the compartment 12. The feeding means comprises a tubular section 18, which is curved. The  
20 curved tubular section is arranged directly adjacent to the inlet, in connection to the circumference 16 of the elongated feeding compartment 12. The tubular section extends substantially in the radial direction R of the elongated feeding compartment 12. The mixture of steam and  
25 fibres, at passage in the curved tubular section 18 is separated during influence of centrifugal forces, in a direction of flow F, in a substantially relatively heavy steam-less fraction of fibres in a radially outer layer 20 that at the inlet is fed peripherally P in the elongated  
30 feeding compartment 12, and in a substantially light fibre-free fraction of steam in a radially inner layer 22 that at the inlet is fed against the centre C of the elongated feeding compartment 12.

As evident from the embodiment of the feeding machine 12 in fig. 1A, the steam that is brought towards the centre of the feeding machine is removed out through an axial outlet 23 arranged at the feeding machine. The fraction of fibres at the periphery of the feeding machine is conveyed further against a subsequent refiner, by way of a conveyor worm 25 arranged in the feeding machine

The feeding means has an elongated outer tubular portion 30 (see fig. 1C), which is adjacent an opposite end 31 compared to the end of the curved tubular section 18 that is connected to the inlet 14. Said outer tubular portion 30 has a substantially straight, linear non-curved extension H that, in the direction of flow F, passes into the curved section towards the inlet 14. The feeding means may extend substantially perpendicular to the longitudinal direction L of the elongated feeding compartment 12 of the apparatus, as shown in the drawings. However, the feeding means can suitably be arranged with a slightly obliquely extension in relation to the longitudinal extension of the apparatus. The inlet 14 is arranged tangentially at the periphery 16 of the elongated feeding compartment 12.

The curved tubular section 18 of the feeding means should have at least a curvature length that results in that all fibres that pass the straight outer portion 30 are caught by the curved section 18. The velocity of the fibres at the inlet may not be too high. By designing the curved section with a certain length of curvature, the curved section is thereby utilized to decrease the velocity of the fibres. Also the length B of the curved section is adapted such that the difference in velocity, between the velocity of the fibres in the feeding means in relation to the velocity of the conveyor worm in the elongated feeding

compartment 12, is minimized. In order to provide for an effective separation of steam and fibres it is desirable, at ideal conditions, that a peripheral velocity for the fraction of steam and fibres at the inlet is substantially equal to the peripheral velocity of steam and fibres in the elongated feeding compartment 12.

Fig. 1B shows an alternative embodiment of the elongated feeding compartment 12 of the apparatus where the steam is removed through a radial outlet 24, instead of the axial outlet 23 in fig. 1A. In that respect the apparatus of fig. 1B comprises an inwards radially extending wall section 26 from an inner surface 16' in the elongated feeding compartment 12, that defines a rear chamber 27 arranged in the elongated feeding compartment 12 to which the radial outlet 24 is connected. The wall section is extending towards the shaft of elongated feeding compartment 12. There is a gap 28, between the outer end of the wall section and the shaft where the steam is flowing by and further out through the radial outlet 24. The fraction of fibres are fed in the opposite direction by means of the conveyor worm 25 and are restrained to be brought into the rear chamber by the wall section.

## Patentkrav

1. Apparatus for separating steam from a mixture of steam and fibres, comprising an elongated feeding compartment (12) having an inlet arranged between the short sides of the elongated feeding compartment and feeding means (10) for feeding a mixture of steam and fibres through said inlet, **characterized in** that the feeding means comprises a tubular section (18) which is curved such that the mixture of steam and fibres during passage in the tubular section (18) is separated during influence of centrifugal forces in a substantially relatively heavy steam-less fraction of fibres in a radially outer layer (20) and in a substantially light fibre-free fraction of steam in a radially inner layer (22), the tubular section is arranged in such a way that heavy fraction of fibres is fed through the inlet peripherally (P) into the elongated feeding compartment of the apparatus, while the separated light fraction of steam is fed through the inlet against the centre (C) of the elongated feeding compartment and removed through an outlet (23,24) of the apparatus.

2. Apparatus according to claim 1, **characterized in** that the tubular section (18) is adapted such that the difference in velocity, between the velocity of the fibres in the feeding means in relation to the velocity of a conveyor worm arranged in the elongated feeding compartment, is minimized.

3. Apparatus according to claim 1 or 2, **characterized in** that the apparatus comprises an inwards radially extending wall section (26) from an inner surface (16') in the elongated feeding compartment, that defines a rear chamber

(27) in the apparatus to which the radial outlet (24) is connected, through which outlet the steam is removed.

4. Apparatus according to any of the preceding claims,  
5 **characterized in** that the feeding means has a substantially straight, linear elongated outer tubular portion (30), having an extension (H), which outer portion (30) is positioned adjacent an opposite end (31) compared to the end of the curved tubular section (18) that is  
10 connected to the inlet (14).

5. Apparatus according to claim 4, **characterized in** that the extension (H) of the feeding means forms an angle between 75-90° in relation to the longitudinal extension  
15 (L) of the apparatus.

6. Apparatus according to any of the preceding claims, **characterized in** that the inlet is arranged tangentially at the periphery (16) of the apparatus.  
20

7. Apparatus according to any of the preceding claims, **characterized in** that the cross-sectional area of the inlet and the feeding means is quadratic or rectangular.

25 8. Feeding means (10) for use in an apparatus as defined in any of the preceding claims, for feeding a mixture of steam and fibres through the inlet of the apparatus, **characterized in** that the feeding means comprises a tubular section (18) which is curved such that the mixture  
30 of steam and fibres during passage in the tubular section (18) is separated during influence of centrifugal forces in a substantially relatively heavy steam-less fraction of fibres in a radially outer layer (20) and in a

substantially light fibre-free fraction of steam in a radially inner layer (22).

9. Feeding means according to claim 8, **characterized in**  
5 that the curved tubular section (18) is adapted such that the difference in velocity, between the velocity of the fibres in the feeding means in relation to the velocity of the fibres within the apparatus, is minimized.

10 10. Feeding means according to claim 8 or 9, **characterized in**  
in that the feeding means has a substantially straight, linear elongated outer tubular portion (30), having an extension (H), which outer portion (30) is adjacent an opposite end (31) compared to the end of the curved  
15 tubular section (18) that is connected to the inlet (14).

11. Feeding means according to any of claims 8-10, **characterized in** that the extension (H) of the feeding means forms an angle between 75-90° in relation to the  
20 longitudinal extension (L) of the apparatus.

12. Feeding means according to any of claims 8-11, **characterized in** that the cross-sectional area of the feeding means is quadratic or rectangular.

25 13. A method for feeding a mixture of steam and fibres to an elongated feeding compartment (12) of an apparatus for separating steam from a mixture of steam and fibres, where the mixture of steam and fibres are fed via a feeding  
30 means (10) through an inlet (14) arranged between the short sides of the elongated feeding compartment, **characterized in** that the feeding means comprises a tubular section (18) which is curved, whereby the mixture of steam and fibres at passage in the tubular section (18)

is brought to separate during influence of centrifugal forces in a substantially relatively heavy steam-less fraction of fibres in a radially outer layer (20) and in a substantially light fibre-free fraction of steam in a radially inner layer (22), the tubular section is arranged in such a way that heavy fraction of fibres is fed through the inlet peripherally (P) into elongated feeding compartment of the apparatus, while the separated light fraction of steam is fed through the inlet against the centre (C) of the elongated feeding compartment and removed through an outlet (23,24) of the apparatus.




Fig. 1C

Fig.1C

## INTERNATIONAL SEARCH REPORT

International application No.

P 03/01614

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: D21B 1/02, D21B 1/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: D21B, D21C, D21D, B27N, B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 8808050 A1 (SUNDS DEFIBRATOR AKTIEBOLAG), 20 October 1988 (20.10.88), figures 1-3, claims 1-7  --	1-13
A	SE 514165 C2 (VALMET FIBERTECH AB), 15 January 2001 (15.01.01), figures 1,2, abstract  -----	1-13

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

15 December 2003

Date of mailing of the international search report

13 -01- 2004

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Wiva Asplund/ELY

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT  
Information on patent family members

31/10/03

International application No.

SE 03/01614

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
WO	8808050	A1	20/10/88	AT 74170 T	15/04/92
				AU 613037 B	25/07/91
				AU 1629488 A	04/11/88
				CA 1308289 A,C	06/10/92
				DE 3869611 A	30/04/92
				EP 0360807 A,B	04/04/90
				SE 0360807 T3	
				FI 87586 B,C	15/10/92
				FI 894876 D	00/00/00
				JP 2503211 T	04/10/90
				NO 173107 B,C	19/07/93
				NO 885548 A	14/12/88
				NZ 224242 A	27/10/89
				SE 468015 B,C	19/10/92
				SE 8701573 A	16/10/88
				US 5034099 A	23/07/91
SE	514165	C2	15/01/01	AU 1303400 A	26/04/00
				AU 4965100 A	05/12/00
				CA 2345698 A	13/04/00
				CA 2371052 A	23/11/00
				EP 1191993 A	03/04/02
				SE 9901752 A	13/11/00
				US 6602310 B	05/08/03
				WO 0069543 A	23/11/00